


FCI/1804/51728

1804/51728

RECD 13 OCT 2004
PCT

PA 1211740



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

September 16, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/505,334

FILING DATE: September 23, 2003

**PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)**




**By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS**



A handwritten signature in dark ink, appearing to read "P. Swain", is written over the printed name.

**P. SWAIN
Certifying Officer**

BEST AVAILABLE COPY

ORDER NUMBER		1211740		Page 1 of 1	
REFERENCE ORDER NUMBER		0			
BIN NUMBER		0			
DELIVERY INSTRUCTIONS					
ORDER DATE/TIME	PALM NUMBER	CUSTOMER NUMBER	CONTACT PHONE NUMBER	PAYMENT METHOD	TOTAL COST OF ORDER
2004/08/09 14:42:00		IDON853063	(440) 483-4281	DEPOSIT ACCOUNT	\$ 20.00
BROADCAST MESSAGE					
Order your copies of USPTO documents on the Web. It's fast, easy, and secure! Go to (http://ebiz1.uspto.gov/oems25p/index.html) and order today! Please provide a copy of this packing slip to your accounting department to assist in reconciling your PTO deposit account records.					
ORDER INFORMATION					
ORDER LINE	PRODUCT TYPE	DOCUMENT IDENTIFIER	COPIES	STATUS	CUSTOMER REFERENCE
1	B3	60505334		FILED	PHUS030354USQ
					
<div><div>E-MAIL</div><div></div><div>FAX NUMBER</div><div>(440) 483-4874</div><div>CARRIER</div><div></div><div>CARRIER TRACKING NUMBER</div><div></div><div>CARRIER ACCOUNT NUMBER</div><div></div></div> <div></div>					

09/23/03
16562 U.S. PTO

PTO/SB/18 (10-01)
Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE.
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

17513 U.S. PTO
60/505334
09/23/03

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No. EK419165869US

INVENTOR(S)					
Given Name (first and middle (if any))	Family Name or Surname		Residence (City and either State or Foreign Country)		
Thomas Laura Sara	CULL GAUL OBERRECHT		Willoughby Hills, Ohio Willoughby, Ohio Cleveland Heights, Ohio		
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (500 characters max)					
METHOD AND APPARATUS FOR OBTAINING CENTER OF K-SPACE DATA					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number		Type Customer Number here		Place Customer Number Bar Code Label here	
OR					
<input checked="" type="checkbox"/> Firm or Individual Name	THOMAS M. LUNDIN				
Address	Philips Intellectual Property & Standards				
Address	595 Miner Road				
City	Cleveland	State	Ohio	ZIP	44143
Country	US	Telephone	440-483-4281	Fax	440-483-4874
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification	Number of Pages	4	<input type="checkbox"/> CD(s), Number		
<input checked="" type="checkbox"/> Drawing(s)	Number of Sheets	2	<input type="checkbox"/> Other (specify)		
<input type="checkbox"/> Application Data Sheet, See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.			FILING FEE AMOUNT (\$)		
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:			14-1270	160.00	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,

SIGNATURE

Tom Lundin

Date 23-Sep-2003

TYPED or PRINTED NAME

THOMAS M. LUNDIN

REGISTRATION NO.
(If appropriate)
Docket Number:

48,979

TELEPHONE

440-483-4281

PHUS030354USQ

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

METHOD AND APPARATUS FOR OBTAINING
CENTER OF K-SPACE DATA

By: Thomas Cull, Laura Gaul, and Sara Oberrecht

5

BACKGROUND

The present invention relates to the field of medical imaging and has particular applicability to magnetic resonance imaging. More specifically, the invention relates to a method and apparatus for obtaining data from the center of k-space, particularly during
10 magnetic resonance angiography acquisitions.

For real-time MR angiography acquisitions, the results are usually obtained by acquiring k-space data in an order based on the proximity of the data points to the center of k-space.

Previous methods typically require some form of data sorting based on the distance
15 from the center of k-space. Some of these sorting algorithms scale in operation as the number of points to the second power, which results in slow computation for typical acquisition slice and phase k-space data sizes can be on the order of 10,000 points or more.

Further, some previous methods tend to have image blurring along an encoding axis, which can lead to incorrect image evaluation.

20

SUMMARY

Those skilled in the art will, upon reading and understanding the appended description, appreciate that aspects of the present invention address the above and other matters.

25

In accordance with one embodiment of the invention, an apparatus is provided to acquire k-space data timed such that low frequency components (e.g. center of k-space) are acquired during a peak of signal enhancement.

In accordance with another embodiment of the invention components from the center of k-space are acquired in relation to a peak of signal enhancement resulting from a
30 contrast agent.

In accordance with another embodiment of the invention, the peak of signal enhancement results from a bolus contrast agent.

One advantage of an embodiment of the invention is that a reduction in sorting k-space is facilitated.

Another advantage of an embodiment of the invention is that it facilitates a reduction in sequence computation.

5 Another advantage of an embodiment of the invention is that it facilitates a reduction in compilation time.

Another advantage of an embodiment of the invention is that reconstruction of slice direction data can be performed upon filling all slice data points for a given phase column.

10 Another advantage of an embodiment of the invention is that a reduction in the latency between scan completion and image reconstruction is facilitated.

Still further advantages of the present invention will become apparent to those of ordinary skill in the art upon a reading and understanding of the following description of the preferred embodiments.

15 DRAWINGS

The invention may take form in various components and arrangements of components, and in various steps and arrangements of steps. The drawings are only for purposes of illustrating a preferred embodiment and are not to be construed as limiting the invention.

20 Figure 1 shows an illustration of a k-space grid indicating an order in which k-space points can be acquired.

Figure 2 shows an illustration of a k-space grid indicating an order in which k-space points can be acquired.

25 DESCRIPTION

Fig. 1 shows a k-space grid 100 including points at which k-space is sampled. In the embodiment shown, the x-axis indicates a phase-encode direction and the y-direction indicates a slice-encode direction. It is to be understood that a read direction can be directed in direction perpendicular to both phase-encode and slice-encode directions.

30 In one embodiment, a first region 200 is defined in the k-space grid. In the embodiment shown the first region includes k-space points 1 through 9. An outer region of

k-space 400 includes the region of k-space within the grid 100 and outside the first region 200.

Fig. 2 shows a k-space grid 100 including points at which k-space is sampled. In the embodiment shown, the x-axis indicates a phase-encode direction and the y-direction indicates a slice-encode direction. It is to be understood that a read direction can be directed in direction perpendicular to both phase-encode and slice-encode directions.

In the embodiment shown in Fig. 2, a first region 200 is defined in the k-space grid. In the embodiment shown the first region includes k-space points 1 through 9. The embodiment shown in Fig. 2 also includes a second region 300 defined in the k-space grid. As can be seen, the second region surrounds the first region. An outer region of k-space 400' includes the region of k-space within the grid 100 and outside the first and second regions.

The slice and phase k-space points are placed in a grid spanning from the most negative to the most positive value along each axis. The distance is measured in k-space units of $1/\text{length}$.

In one embodiment, acquisition data points are placed in an array that indicates the order in which k-space points are acquired.

K-space is divided into regions, for example circular regions, based on given distances. The first region can be defined by all points that are less than or equal to a given distance A. The second region can be defined by points that are outside of the distance A, but less than or equal to a next distance B. This division can continued for as many rings as desired.

The radius of the first region is based on the time desired to fill the central section. K-space points that lie within the bounds of the central ring will be acquired in the first group. K-Space points that lie within the second region will be acquired in the second group, and so on. The last group acquired lies outside the defined rings. The order of the points within each annulus is determined by the order of evaluation. For example in sequential order as shown in Fig. 1 and Fig. 2.

In one embodiment, the slice-phase k-space data points are evaluated in each pass center-out along the phase direction and serpentine along the slice direction. If the distance is less than or equal to the distance defining the central region, the data point's index is added to the k-space order array.

When all points in k-space have been examined the next ring or annulus is evaluated in the same manner. The points already used are skipped.

In another embodiment, the central region can be shuffled into random order, such that the very central point occurs in the middle half of the time to fill the central ring
5 region.

In another embodiment, the evaluation order can take on other forms such as sequential or center-out in both directions.

In another embodiment, acquisition may be designed to depend on the timing of contrast bolus or acquisition time.

10 The invention has been described with reference to the preferred embodiment. Obviously, modifications and alterations will occur to others upon reading and understanding the preceding description. It is intended that the invention be construed as including all such modifications and alterations insofar as they come within the scope of the appended claims or the equivalents thereof.




Fig. 1




Fig. 2

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.